



SC Onyx UV DTF Film

ROLL PRINTING

A FILM

Printing Film

- 24" x 100m

B FILM

Transfer Film

- 24" x 100m



SHEET PRINTING

A FILM

Printing Film

- 11.7" x 16.5"

B FILM

Transfer Film

- 11.7" x 50m



FEATURES

- **No Sticky Glue Residues**
- **More Rigid Glue Surface**
- **Strong Adhesion**
- **High Washing Durability**

When you peel off the protective film of A film.

Doesn't come off when you touch the A film.

About 1600~2000 gf / other brands average : 800~1000 gf

Dish washer safe

Apply on glassware, plastic, ceramic, wood, leather materials etc...



TORONTO
1-647-220-8000

www.spectrumcolors.com

VANCOUVER
1-437-499-7000

info@spectrumcolors.com




SC Onyx UV DTF Film

PROCESS

Step.1 Peel Off The Protective Film

Place the A film (printing film) on a UV or UV DTF printer and carefully peel off the protective film.



A Film
Printing Side
(Sticky)

Protective
Film

Step.2 Print With UV Printer

Print artwork on the sticky side of A film with UV printer.

Step.3 Cold Laminating

Cover the printed artwork with glossy side of B film (transfer film) facing down.



Step.4 Cut The Artwork And Peel Off The B Film

Only the artwork will be transferred.

Step.5 Transfer Onto The Rigid Surface



① Clean the surface with alcohol.



② Place the B film onto the rigid surface.



③ For materials that do not transferred well like plastic or ceramic, use a hair dryer or heat gun to slightly melt the glue.



④ Peel off the film.



TORONTO
1-647-220-8000

www.spectrumcolors.com

VANCOUVER
1-437-499-7000

info@spectrumcolors.com